

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1-2. (Canceled)

3. (Previously Presented) An attachment with a clip, which attachment includes at least two storage parts each formed by a synthetic resin sheet material and each having peripheral edges sealed except for an opening part, one of the storage parts storing an object used according to a purpose, the other storage part including at least the clip by inserting and attaching a clipping one end portion of the clip, which portion is formed by bending a wire material to form a generally U shape and bending upper ends of the generally U shape inward or outward to be parallel to an inside or outside of the generally U shape, into the other storage part, a clipping other end portion of the clip serving as a locking part locked at an attachment target, the attachment target held between the locking part and the storage part side.

4. (Previously Presented) An attachment with a clip, which attachment includes at least two storage parts each formed by a synthetic resin sheet material and each having peripheral edges sealed except for an opening part, a ventilation part formed in one of the storage parts and the one storage part storing a material that contains an emanative component such as a volatile component, the other storage part including at least the clip by inserting and

attaching a clipping one end portion of the clip, which portion is formed by bending a wire material to form a generally U shape and bending upper ends of the generally U shape inward or outward to be parallel to an inside or outside of the generally U shape, into the other storage part, a clipping other end portion of the clip serving as a locking part locked at an attachment target, the attachment target held between the locking part and the storage part side.

5. (Previously Presented) An attachment with a clip, wherein at least two synthetic resin sheet materials are laminated on a rear side of a front sheet material consisting of synthetic resin, peripheral edges are sealed except for an opening part to form storage parts, the front sheet material-side storage part serving as a storage part that stores an object used according to each purpose, the object being freely output and input, the rear storage part serving as an attachment part, a clipping one end portion of the clip, which portion is formed by bending a wire material to form a generally U shape and bending upper ends of the generally U shape bent inward or outward to be parallel to an inside or outside of the generally U shape, inserted into at least the attachment part, a clipping other end portion of the clip serving as a locking part locked at an attachment target, the attachment target held between the locking part and the storage part side.

6. (Previously Presented) An attachment with a clip, wherein at least two synthetic resin sheet materials are laminated on a rear side of a front sheet material consisting of synthetic resin, peripheral edges are sealed except for an opening part to form storage parts, the

front sheet material-side storage part storing a material that contains an emanative component such a volatile component with the opening part closable except for the ventilation part, a clipping one end portion of the clip, which portion is formed by bending a wire material to form a generally U shape and bending upper ends of the generally U shape inward or outward to be parallel to an inside or outside of the generally U shape, inserted into at least the rear storage part, a clipping other end portion of the clip serving as a locking part locked at an attachment target, the attachment target held between the locking part and the storage part side.

7. (Previously presented) The attachment with the clip according to claim 3, wherein the rear storage part out of the two storage parts is constituted to form clip insert storage parts is constituted to form clip insert storage parts on both sides, respectively, or constituted to be formed as the clip insert storage parts located on both side.

8. (Currently Amended) The attachment with the clip according to claim ~~4~~3, wherein a data transmittable and receivable IC chip is stored in the storage part.

9-12. (Canceled)